

Performance Data

• MICRON RATING: 15.00 NOMINAL

• BETA RATING: N/A

COLLAPSE PRESSURE RATING: N/A
MAXIMUM TEMPERATURE: 250 F

• DIRECTION OF FLOW: OUTSIDE->IN

• RECOMMENDED CHANGEOUT DIFFERENTIAL

PRESSURE: 20 PSID

Dimensional Specifications

• (A) OUTER DIAMETER, TOP: 7.94 IN (201.68 MM)

• (B) OUTER DIAMETER, BOTTOM: 7.93 IN (201.42 MM)

• (C) INNER DIAMETER, TOP: 5.38 IN (136.65 MM)

• (D) INNER DIAMETER, BOTTOM: 0.67 IN (17.02 MM)

• (E) LENGTH: 16.38 IN (17.02 MM)

• (F) THREAD: NONE

Physical Specifications

• HANDLE: NONE

• SEAL MATERIAL: BUNA-N

• TYPE OF ADHESIVE: PLASTISOL

• TYPE OF ENDCAP: PLATED STEEL

CENTER TUBE: PLATED STEEL

• TYPE OF MEDIA: PAPER

• FILTER AREA: SQ.IN.

• PLATING: NONE

• OUTER JACKET: YES - METAL

• CONFIGURATION: SINGLE OPEN END/BH

Packaging Specifications

• NUMBER PER CARTON: 1

• CARTON WEIGHT: 5.20 LB (2.36 KG)

