

## Performance Data

- Micron Rating:
- Beta Rating:
- N/A
- Collapse Pressure Rating: 75 PSID
- Maximum Temperature: 150 F
- Direction of Flow: OUTSIDE->IN
- Recommended Changeout Differential Pressure: 20 PSID



## Dimensional Specifications

- (A) Outer Diameter, Top: 12.75 IN (323.85 MM)
- (B) Outer Diameter, Bottom: 12.75 IN (323.85 MM)
- (C) Inner Diameter, Top: 8.38 IN (212.85 MM)
- (D) Inner Diameter, Bottom: 0.57 IN (14.48 MM)
- (E) Length: 26.00 IN (14.48 MM)
- (F) Thread: NONE

## Physical Specifications

- Handle: NONE
- Seal Material: BUNA-N
- Type of Adhesive: PLASTISOL
- Type of Endcap: PLATED STEEL
- Center Tube: PLATED STEEL
- Type of Media: 80/20 BLEND FR
- Filter Area: 226 SQ.FT. Plating: ELECTRO-GALVANIZED
- Outer Jacket: YES - METAL
- Configuration: SINGLE OPEN END/BH

## Packaging Specifications

- Number per Carton: 1
- Carton Weight: 15.00 LB (6.80 KG)