

Performance Data

- Micron Rating: 0.50 NOMINAL
- Beta Rating: 0.999
- Collapse Pressure Rating:
- Maximum Temperature: 150 F
- Direction of Flow: OUTSIDE->IN
- Recommended Changeout Differential Pressure: 20 PSID



Dimensional Specifications

- (A) Outer Diameter, Top: 13.88 IN (352.55 MM)
- (B) Outer Diameter, Bottom: 13.88 IN (352.55 MM)
- (C) Inner Diameter, Top: 9.48 IN (240.79 MM)
- (D) Inner Diameter, Bottom: 9.48 IN (240.79 MM)
- (E) Length: 25.96 IN (240.79 MM)
- (F) Thread: NONE Physical Specifications
- Handle: NONE
- Seal Material: POLYISOP
- Type of Adhesive: PLASTISOL
- Type of Endcap: G60 GALVANIZED STEEL
- Center Tube: G60 GALVANIZED STEEL
- Type of Media: 80/20 FIRE RET
- Filter Area: 255 SQ.FT.
- Plating: NONE
- Outer Jacket: YES – METAL
- Configuration: DOUBLE OPEN END

Packaging Specifications

- Number per Carton: 1
- Carton Weight: 20.00 LB (9.07 KG)