
Performance Data



- Micron Rating: 3.00 NOMINAL
- Beta Rating: N/A
- Collapse Pressure Rating: 75 PSID
- Maximum Temperature: 150 F
- Direction of Flow: INSIDE->OUT
- Recommended Changeout Differential Pressure: 20 PSID

Dimensional Specifications

- (A) Outer Diameter – Top: 12.75 IN (323.85 MM)
- (B) Outer Diameter – Bottom: 12.75 IN (323.85 MM)
- (C) Inner Diameter – Top: 8.38 IN (212.85 MM)
- (D) Inner Diameter – Bottom:
- (E) Length: 22.00 IN (30.23 MM)
- (F) Thread: NONE

Physical Specifications

- Handle: NONE
- Seal Material: NEOPRENE
- Type of Adhesive: PLASTISOL
- Type of Endcap: G60 GALVANIZED
- Center Tube: G60 GALVANIZED EXP.
- Type of Media: 80/20 BLEND
- Filter Area: 145 SQ.FT.
- Plating: ELECTRO-GALVANIZED
- Outer Jacket: YES – METAL
- Configuration: SINGLE OPEN END/BH

Packaging Specifications

- Number per Carton: 1
- Carton Weight: 14.00 LB (6.35 KG)